
# Jump Distance Based Synthetic Disk Access Patterns

Zachary Kurmas and Jeremy Zito Grand Valley State University

# New storage systems must be evaluated with respect to many different workloads



An design may be **good** for some workloads and **bad** for others.

### Sources of Evaluation Workloads


#### Trace of real workloads

- List of I/O requests made by production workload
- Accurate
- Large
- Inflexible
- Difficult to obtain(due to security concerns)

### Synthetic workloads


- Randomly generated model of some workload
- Usually Inaccurate
- Compact representation
- Easily modified
- Compact representation contains no specific data

# My goal: Accurate synthetic workload




# \$64,000 question: What goes in here?

# Jump Distance




- Our poster presents a synthetic workload generation technique called "Jump Distance"
- Each jump distance approximates distance traveled by disk head
- Goal: Synthetic and target workloads make disk heads move the same amount




# NP-Complete Problem

Problem: If we also require that the synthetic workload maintain the same distribution of sectors accessed, the problem becomes a form of the NP-Complete Hamiltonian Path problem.




## Solution

- Perform depth-first search for Hamiltonian Path
- Complete path represents synthetic disk access pattern with identical jump distance and location distributions



## Solution #2

Partial path completed randomly for an approximate solution



### Results

- Partial paths average just under 80% of maximum length
- Resulting Jump Distance distributions not perfectly accurate, but reasonably accurate
- Results in reasonably accurate synthetic workloads --- if workload behavior dominated by disk head movement